



1TH9-SP/OG

90° 弯英锥管外螺纹 / 公制外螺纹轻系列 ISO 6149-3
 90° ELBOW BSPT MALE / METRIC MALE L-SERIES ISO 6149-3

代号 PART NO.	螺纹 THREAD		O形圈 O-RING		尺寸 DIMENSIONS				
	E	F		F端	A	B	S1	S2	
1TH9-02-10SP/OG	R1/8"X28	M10X1		8.1X1.6	21	26.5	11	14	
1TH9-02-12SP/OG	R1/8"X28	M12X1.5		9.3X2.4	21	32	11	17	
1TH9-04-12SP/OG	R1/4"X19	M12X1.5		9.3X2.4	25.5	32	14	17	
1TH9-04-14SP/OG	R1/4"X19	M14X1.5		11.3X2.4	25.5	32	14	19	
1TH9-04-18SP/OG	R1/4"X19	M18X1.5		15.3X2.4	28	37	19	24	
1TH9-06-14SP/OG	R3/8"X19	M14X1.5		11.3X2.4	28.5	34	16	19	
1TH9-06-16SP/OG	R3/8"X19	M16X1.5		13.3X2.4	28.5	34.8	16	22	
1TH9-08-18SP/OG	R1/2"X14	M18X1.5		15.3X2.4	36	39.5	22	24	
1TH9-08-20SP/OG	R1/2"X14	M20X1.5		17.3X2.4	36	40	22	27	
1TH9-08-22SP/OG	R1/2"X14	M22X1.5		19.3X2.4	36	40.2	22	27	
1TH9-12-22SP/OG	R3/4"X14	M22X1.5		19.3X2.4	43.5	43.5	27	27	
1TH9-12-27SP/OG	R3/4"X14	M27X2		23.5X3	43.5	48.5	27	32	
1TH9-16-27SP/OG	R1"X11	M27X2		23.5X3	50	52	33	32	
1TH9-16-33SP/OG	R1"X11	M33X2		29.2X3	50	52.5	33	41	
1TH9-20-42SP/OG	R1.1/4"X11	M42X2		38.5X3	56.5	57.2	41	50	
1TH9-24-48SP/OG	R1.1/2"X11	M48X2		44.5X3	62.5	62.7	48	55	

注：可与ISO 9974-1油口相配，去掉挡圈与ISO 6149-1油口相配。
 Note: fit for ISO 9974-1 port or ISO 6149-1 port when useless of retaining ring.